ROVITEC

ROVITEC PRODUCT DOCUMENT

DISTRIBUTION COPY

FIFISH E-GO technical specifications

QYSEA

Distributed by ROVITEC AS

rovitec.no

Document type: datasheet

Reviewed: 2026-09-15

The original producer pages follow unchanged.

ROVITEC distributes this document for product information. Technical specifications remain the producer's.

Original source reference:

https://drive.google.com/uc?export=download&id=1eU7OXajMMCTbBH9peyu1MW-KsYAIjHfN

qysea-fifish-e-go-technical-specifications.pdf

FIFISH E-GO
Technical Specifications



ROV

Dimensions	430mm(l) x 345mm(w) x 170mm(h)
Weight	5.9kg
Depth Rating	100m
Payload	5kg
Speed	>3 Knots (>1.5 m/s)
Propellers	6 Degree of Freedom
	Movement: left & right, up & down, forward & backward, 360° yaw, 360° pitch, 360° roll
	Hard Anodized Aluminum Alloy
Operating Temp.	-10 °C ~ 60 °C (Operational Temp. Range)
Power	1-4h (Dependent on Work Environment)
	69.12wh * 2 Capacity
	Hot-Swappable Power System
	Smart Battery Management
	Quick Charging: 90% Full Power in 1h (Actual Charging Speed May Differ)

Sensors

Gyroscope	±0.1°	Posture Lock: ± 0.1° pitch angle or ± 0.1° roll angle, moving in any direction
Accelerometer	±0.1°	
Magnetometer	±1°	
Depth Sensor	Suspension within ±1 cm	Depth Lock
Temp. Sensor	±1°	

Camera

Sensor	1/1.8″
Pixels	12MP
Aperture	f/2.5
Field of View	Above Water: 176° Underwater: 146°
Focus Range	0.1m~ + ∞
Shutter Speed	5-1/5000 Second
Burst Shooting	1/3/5/10 Frames
ISO	100–3200 (Auto/Manual)
White Balance	2500K-7500K (for Seawater & Freshwater, Auto/Manual)
Exposure Compensation	-3.0 EV to +3.0 EV (Auto/Manual)
Photo Resolution	4:3 = 4000 × 3000 16:9 = 3840 × 2160
Photo Format	JPEG, DNG
Video Resolution	4K UHD: 25/30 fps
	1080p FHD: 25/30/50/60/75/90 fps
	720P HD: 25/30/50/60/75/90 fps
Video Encode	H.264
Video Format	MP4
Stabilization	Electronic Stabilization (EIS)
Color System	NTSC & PAL
Internal Storage	External MicroSD Storage (128GB Standard, Supports up to 512GB)
AI Vision Functionality	Vision Lock, Diver Tracking, Imaging Dehazing

Lighting

Brightness	5000 Lumen LED * 2
CCT	5500K
Beam Angle	160°
Brightness Levels	3

Please contact the QYSEA team for more details;
specifications are subjected to change without notice.

QYSEA

FIFISH E-GO
Technical Specifications



Charger

ROV	Input: 100-240V, 50/60 Hz, 2.5A MAX
	Output: 18V ⎓ 10A
Controller	Input: 100-240V, 50/60 Hz, 0.5A MAX
	Output: 5V ⎓ 3A

Port Interface

Quantity	2 Ports, Expandable to 4 Ports (Extension Dock Required)
Material	Stainless steel 316
Interface	11V-24V @ 5A ETHERNET, UART
Adjustable Power	Adaptive Voltage Range for External Add-on Accessories
Secure Plug	Self-diagnostic Tests & Leakage Prevention

Controller

Wireless Network	5GHz WiFi: 802.11a/n/ac
Usage Time	Up to 4 hours
File Download Format	MicroSD Card: FAT32 & EXFAT (128GB Max. Storage Support)
HDMI Output	HDMI Box Required

Tether & Spool

Cable length	100m/ 200m
Tensile strength	130kgf
Cable Diameter	4.6mm
Tether Weight (Underwater)	Neutral Buoyancy
Waterproof Rating	IP65

Please contact the QYSEA team for more details;
specifications are subjected to change without notice.

QYSEA